



SAFETY DATA SHEET

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH) & 1272/2008 (CLP)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier**
Product Name Tech Quick Fix Chemical Cement
Product Code(s) 1784, 1785, 1786
- 1.2 Relevant identified uses of the substance or mixture and uses advised against**
Identified use(s) Rubber Adhesive
Product is for professional use only
Uses advised against None identified
- 1.3 Details of the supplier of the Safety Data Sheet**
Company Identification Tech Europe
15 Ballinderry Road
Lisburn
BT28 2SA
UK
Telephone +44 2892 665721
E-Mail (competent person) info@eurotyrerepair.com
- 1.4 Emergency telephone number**
Emergency Phone No. +44 2892 665721 (08.00 – 16.30 GMT Monday to Friday)
+1 703 527 3887 (Chemtrec – U.S. All other times)

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture**
- 2.1.1 Regulation (EC) No. 1272/2008 (CLP)** Flam. Liq. 2, Asp.Tox.1, Aquatic Chronic 2,
Skin Irrit. 2; STOT SE 3
- 2.1.2 Directive 67/548/EEC & Directive 1999/45/EC** F: Highly flammable
Xn:Harmful
Xi: Irritant



2.2 Label elements

2.2.1 Label elements

Hazard Pictogram(s)

According to Regulation (EC) No. 1272/2008 (CLP)



Signal word

Danger

Hazard statement(s)

H225: Highly flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

Precautionary statement(s)

P101: If medical advice is needed, have product container or label at hand.

P210: Keep away from heat, sparks, open flame, hot surfaces
- No smoking

P241: Use explosion-proof electrical/ventilating/lighting equipment.

P273: Avoid release to the environment.

P281: Use personal protective equipment as required.

P301 + P310: IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.

P303+P361+P353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

P403 + P233: Store in a well-ventilated place. Keep container tightly closed.

P501: Dispose of contents/container to: hazardous waste site
According to Directive 67/548/EEC & Directive 1999/45/EC

2.2.2 Label elements

Hazard Symbol



Risk Phrases

R11: Highly flammable

R38: Irritating to skin

R43: May cause sensitisation by skin contact

R52/53: Harmful to aquatic organisms, may cause long term adverse effects in the aquatic environment

R65: Harmful: may cause lung damage if swallowed

R67: Vapours may cause drowsiness and dizziness

Safety Phrases

S7/9 - Keep container tightly closed and in a well-ventilated place.

S16 - Keep away from sources of ignition - No smoking.

S36/37 - Wear suitable protective clothing and gloves.

S45 - In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).



S53 - Avoid exposure - obtain special instructions before use.
S60 - This material and its container must be disposed of as hazardous waste.

2.3 Other hazards

None

2.4 Additional Information

None

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

EC Classification No. 1272/2008

Hazardous ingredient(s)	%W/W	CAS No.	EC No.	REACH Registration No.	Hazard pictogram(s) and Hazard statement(s)
Solvent naphtha (petroleum), light aliphatic	90 - 100	64742-89-8	265-192-2	05-2114107985-43	Aquatic Chronic 2, H411 Asp. Tox. 1, H304 Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE3, H336
N-Ethylcyclohexylamine	1 - 5	5459-93-8	226-733-8	Not available	Acute Tox. 4, H302+332 Flammable Liq. 3, H226 Acute Tox. 3, H311 Skin Corr./Irrit. 1B, H314

EC Classification No. 67/548/EEC

Hazardous ingredient(s)	%W/W	CAS No.	EC No.	REACH Registration No.	EC Classification and Risk Phrases
Solvent naphtha (petroleum), light aliphatic	90 - 100	64742-89-8	265-192-2	05-2114107985-43	F, Xn, N R11, R38, R51/53, R65, R67
N-Ethylcyclohexylamine	1 - 5	5459-93-8	226-73-8	Not available	Xn, C R10 R20/21/22 R35

3.3 Additional Information

For full text of H/P phrases see section 16.

According to Note P in Regulation EC 1272/2008 "The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

According to Note P in Regulation 67/548/EEC "The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."



SECTION 4: FIRST AID MEASURES



4.1 Description of first aid measures

Inhalation

Remove persons affected by vapour to fresh air.

For those providing assistance, avoid exposure to yourself or others.

If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance.

If breathing is irregular or has stopped, administer artificial respiration.

Skin Contact

Remove contaminated clothing and wash affected skin with water. Wash contaminated clothing before reuse.

Eye Contact

If substance has got into the eyes, immediately wash out with plenty of water until medical assistance is provided.

Ingestion

If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

4.2 Most important symptoms and effects, both acute and delayed

Headache, dizziness, drowsiness, nausea, and other CNS effects. Numbness, muscle cramps, weakness and paralysis that may be delayed. Itching, pain, redness, and swelling of skin.

4.3 Indication of immediate medical attention and special treatment needed

If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately. This mixture may be associated with cardiac sensitization following very high exposures (well above occupational exposure limits) or with concurrent exposure to high stress levels or heart-stimulating substances like epinephrine. Administration of such substances should be avoided. Individuals with pre-existing neurological disease should avoid exposure.

SECTION 5: FIRE-FIGHTING MEASURES

5.1 Extinguishing Media

Suitable Extinguishing Media

Extinguish with dry chemical, foam or carbon dioxide.

Unsuitable Extinguishing Media

Straight streams of water

5.2 Special hazards arising from the substance or mixture

Toxic to aquatic life with long lasting effects.

Burning produces obnoxious and toxic fumes. In the event of fire the following can be released: carbon oxides; hydrocarbons; nitrogen oxides (NO_x); sulphur oxides; and metal oxides

5.3 Advice for fire-fighters

Evacuate area. If a leak or a spill has not ignited, use water spray to disperse the vapours and to protect personnel attempting to stop a leak. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply. Fire-fighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.



SECTION 6: ACCIDENTAL RELEASE MEASURES

- 6.1 Personal precautions, protective equipment and emergency procedures** Avoid contact with spilled material. Wear suitable protective equipment. Refer to section 5 for fire-fighting; section 4 for first-aid advice; and section 8 for minimum requirements for personal protective equipment.
- 6.2 Environmental precautions** Do not allow to enter drains, sewers or watercourses.
- 6.3 Methods and material for containment and cleaning up** Eliminate sources of ignition. Shut off leaks if without risk. Adsorb spillages onto sand, earth or any suitable adsorbent material.
- 6.4 Reference to other sections** See 6.1
- 6.5 Additional Information** None

SECTION 7: HANDLING AND STORAGE

- 7.1 Precautions for safe handling** Avoid contact with skin. Avoid breathing fumes. Avoid ingestion. Avoid inhalation of vapours. Use only with adequate ventilation. Keep away from heat and sources of ignition. Keep container tightly closed. Wear protective gloves/clothing and eye/face protection.
- 7.2 Conditions for safe storage, including any incompatibilities**
- | | |
|------------------------|---|
| Storage Temperature | Ambient |
| Storage Pressure | Ambient |
| Incompatible materials | Natural rubber; Butyl rubber; EPDM; Polystyrene |
- 7.3 Specific end use(s)** Section 1.2 informs about identified end uses.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

- 8.1 Control parameters**
- 8.1.1 Occupational Exposure Limits**

SUBSTANCE.	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m ³)	STEL (ppm)	STEL (mg/m ³)	Note:
n- Hexane	110-540-3	20	72	Not available	Not available	EH 40

- 8.1.2 Biological limit value** Not established

- 8.1.3 PNECs and DNELs**

DNEL	Oral	Inhalation	Dermal
Industry - Long Term – Local effects	Not available	Not available	Not available
Industry - Long Term - Systemic effects	Not available	Not available	Not available
Industry - Short term - Local effects	Not available	Not available	Not available
Industry - Short term - Systemic effects	Not available	Not available	Not available
Professional - Long Term - Local effects	Not available	Not available	Not available
Professional - Long Term – Systemic effects	Not available	Not available	Not available
Professional - Short term - Local effects	Not available	Not available	Not available
Professional - Short term - Systemic effects	Not available	Not available	Not available
Consumer - Long Term - Local effects	Not available	Not available	Not available
Consumer - Long Term - Systemic effects	Not available	Not available	Not available
Consumer - Short term - Local effects	Not available	Not available	Not available
Consumer - Short term - Systemic effects	Not available	Not available	Not available



PNEC	
Aquatic Compartment	Not available
Terrestrial Compartment	Not available
Atmospheric Compartment	Not available

8.2 Exposure controls

8.2.1 Appropriate engineering controls

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Control measures to consider: Adequate ventilation so that exposure limits are not exceeded.

8.2.2 Personal protection equipment

Eye/face protection



Wear chemical safety glasses with side shields, or splash-proof goggles

Skin protection (Hand protection/ Other)



Any specific glove information provided is based on published literature and glove-manufacturer data. Contact the glove manufacturer for glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. Chemical resistant gloves are recommended. If contact with forearms is likely, wear gauntlet –style gloves. Nitrile, CEN standards EN 420 and EN 374 provide general requirements and list of glove types. If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements. Types of respirator to be considered for this mixture include: Half-face filter respirator; Type A filter material CEN standards EN136, EN140 and EN 405 provide respirator masks and EN 149 and EN 143 provide filter recommendations.

Respiratory protection



Specific hygiene measures

Wash thoroughly after handling. When using do not eat, drink or smoke. Routinely wash work clothing and protective equipment. Discard contaminated clothing and footwear that can not be cleaned. Practice good housekeeping.

8.2.3 Environmental Exposure Controls

See sections 6,7,12,13

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	Liquid (High Viscosity)
Colour	Light Amber
Odour	Paraffinic/strong solvent
Odour Threshold (ppm)	No data available
pH (Value)	No data available
Melting Point (°C) / Freezing Point (°C)	No data available
Boiling point/boiling range (°C):	98.3 – 110° C
Flash Point (°C)	-6.7°C (Closed Cup)
Evaporation rate	3.2 (BuAe=1)
Flammability (solid, gas)	No data available
Explosive limit ranges.	1.1 – 7.5 (%vol)
Vapour Pressure (mm Hg)	38 mmHg @ 20°C
Vapour Density (Air=1)	3.3
Density (g/ml)	0.75 @ 20°C
Solubility (Water)	<0.1 g/l



	Solubility (Other)	Soluble in most organic solvents
	Partition Coefficient (n-Octanol/water)	No data available
	Auto Ignition Temperature (°C)	Not available
	Decomposition Temperature (°C)	No data available
	Viscosity	400cps@ 25°C
	Explosive properties	No data available
	Oxidising properties	No data available
9.2	Other information	Volatility: 93.9%

SECTION 10: STABILITY AND REACTIVITY

10.1	Reactivity	Stable under normal conditions of use
10.2	Chemical stability	Stable under normal conditions
10.3	Possibility of hazardous reactions	Not expected
10.4	Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources
10.5	Incompatible materials	Oxidising agents, acids
10.6	Hazardous Decomposition Product(s)	Burning produces obnoxious and toxic fumes. In the event of fire the following can be released: carbon oxides; hydrocarbons; nitrogen oxides (NOx); sulphur oxides; and metal oxides

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

11.1.2 Mixtures

Acute toxicity	No data is available on the mixture itself. The product contains the following substance which is hazardous for health: Solvent naphtha (petroleum) light aliphatic. Oral toxicity : expected to be of low toxicity: LD50 > 2000mg/kg, Rat Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal. Dermal toxicity: expected to be of low toxicity: LD50 > 2000mg/kg, Rat Inhalation toxicity: expected to be of low toxicity: LC50 > 20mg/l/ 4 hours, Rat. High concentrations may cause CNS depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death.
Irritation	Skin irritation: causes skin irritation. Prolonged/repeated contact may cause de-fatting of the skin which can lead to dermatitis. Eye irritation: expected to be non-irritating to eyes. Vapours may be irritating to the eyes. Insufficient to classify. Respiratory irritation: inhalation of vapours or mists may cause irritation to the respiratory system. Moderately irritating to skin with prolonged exposure
Corrosivity	Not expected to be a skin or respiratory sensitiser
Sensitisation	Causes damage to organs through prolonged or repeated exposure. Repeated exposure affects the CNS.
Repeated dose toxicity	No evidence.
Carcinogenicity	No evidence.
Mutagenicity	No toxicity to reproduction.
Toxicity for reproduction	Exposure to very high concentrations of similar materials has been associated with irregular heart rhythms and cardiac arrest.

11.2 Other information




SECTION 12: ECOLOGICAL INFORMATION

12.1	Toxicity	No data is available on the mixture itself. The product contains the following substance which is hazardous for the environment: Solvent naphtha (petroleum) light aliphatic. The acute toxicity of Solvent naphtha (petroleum), light aliphatic is (IUCLID): Toxicity to algae - EC50/72h/algae = 4700 mg/L
12.2	Persistence and degradability	The mixture itself has not been tested
12.3	Bioaccumulative potential	The mixture itself has not been tested
12.4	Mobility in soil	The mixture itself has not been tested
12.5	Results of PBT and vPvB assessment	The mixture does not contain a substance that is a PBT or a vPvB
12.6	Other adverse effects	None

SECTION 13: DISPOSAL CONSIDERATIONS

13.1	Waste treatment methods	Handle in accordance with good industrial hygiene and safety practice. Refer to protective measures listed in sections 7 and 8. Empty containers retain residue (liquid and/or vapour) and can be dangerous. Do not burn, or use a cutting torch on, the empty drum. Dispose of in accordance with the European Directives on waste and hazardous waste. Waste must be classified and labelled prior to recycling or disposal. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used.
13.2	Additional Information	None

SECTION 14: TRANSPORT INFORMATION

14.1	Land transport (ADR/RID)	
	UN number	UN 1133
	Proper Shipping Name	Adhesives (Solvent naphtha (petroleum), light aliphatic)
	Transport hazard class(es)	3
	Packing Group	II
	Hazard label(s)	
	Environmental hazards	Yes
	Special precautions for user	Not available
	Additional information	None
14.2	Sea transport (IMDG)	
	UN number	UN 1133
	Proper Shipping Name	Adhesives (Solvent naphtha (petroleum), light aliphatic)
	Transport hazard class(es)	3
	Packing Group	II
	Marine Pollutant	Yes
	Special precautions for user	Not Available
	Additional information	None
14.3	Air transport (ICAO/IATA)	
	UN number	UN 1133
	Proper Shipping Name	Adhesives (Solvent naphtha (petroleum), light aliphatic)
	Transport hazard class(es)	3



Packing Group	II
Environmental hazards	Yes
Special precautions for user	Not available
Additional information	None
14.4 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not available

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture	1907/2006 – REACH 1272/2008 – CLP 67/548/EEC – DSD 199/45/EC – DPD 2004/42/CE – Limitations on emissions of volatile organic compounds due to the use of organic solvents in vehicle refinishing products
15.1.1 EU regulations	
Authorisations and/or restrictions on use	Refer to EU regulation for details of any actions or restrictions by the above regulations or directives
15.1.2 National regulations	Refer to national regulation for details of any actions or restrictions by the above regulations or directives
15.2 Chemical Safety Assessment	A Chemical Safety Assessment has not been carried out for this mixture

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

LEGEND

LTEL	Long Term Exposure Limit
STEL	Short Term Exposure Limit
STOT	Specific Target Organ Toxicity
DNEL	Derived No Effect Level
PNEC	Predicted No Effect Concentration
PBT	Persistent bioaccumulative toxic
vPvB	Very persistent very bioaccumulative

References: Sources of information used in preparing this SDS included one or more of the following: results from in-house or supplier toxicology studies; publications from trade associations; ECHA publications; EU guidelines and other sources as appropriate

Risk Phrases and Safety Phrases

R10: Flammable
R11: Highly flammable
R35: Causes severe burns
R38: Irritating to skin.
R43: May cause sensitisation by skin contact
R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R51/53: Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment
R65: Harmful: may cause lung damage if swallowed
R67: Vapours may cause drowsiness and dizziness
S7/9 - Keep container tightly closed and in a well-ventilated place.
S16 - Keep away from sources of ignition - No smoking.
S36/37 - Wear suitable protective clothing and gloves.
S45 - In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
S53 - Avoid exposure - obtain special instructions before use.
S60 - This material and its container must be disposed of as hazardous waste.



Hazard statement(s) and Precautionary statement(s)

H225: Highly flammable liquid and vapour.
H226: Flammable liquid and vapour.
H302+332: Harmful by inhalation and if swallowed.
H304: May be fatal if swallowed and enters airways.
H311: Toxic in contact with skin.
H314: Causes severe skin burns and eye damage.
H315: Causes skin irritation.
H336: May cause drowsiness or dizziness.
H411: Toxic to aquatic life with long lasting effects.
P101: If medical advice is needed, have product container or label at hand.
P210: Keep away from heat, sparks, open flame, hot surfaces - No smoking
P241: Use explosion-proof electrical/ventilating/lighting equipment.
P273: Avoid release to the environment.
P281: Use personal protective equipment as required.
P301 + P310: IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.
P303+P361+P353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P403 + P233: Store in a well-ventilated place. Keep container tightly closed.
P501: Dispose of contents/container to hazardous waste site

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Tech Europe gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Tech Europe accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.